



150# FLANGED END ROTOR VALVES, 2 THRU 5-WAY											
VALVE SIZE	A	B	C	D	E	F	G	H	I		
									S-	L-, T-, B-	LL
1/2"	3.88	2.75	.73	.73	2.44	4.88	2.44	1.50	.500	.375	.250
3/4"	5.06	3.50	.94	.94	2.94	5.88	2.94	1.87	.750	.688	.500
1"	5.31	3.50	1.33	1.33	2.88	5.75	2.88	2.38	1.000	1.000	.750
1 1/4"	5.31	3.50	1.33	1.33	3.00	6.00	3.00	2.38	1.000	1.000	.750
1 1/2"	8.00	4.50	1.56	1.56	3.50	7.00	3.50	2.88	1.500	1.500	1.125
2"	12.00	5.25	1.83	1.83	3.88	7.75	3.88	3.69	2.000	1.875	1.312
2 1/2"	12.00	6.50	2.37	2.37	4.75	9.50	4.75	4.17	2.500	2.500	2.500
3"	18.00	7.75	2.77	2.77	5.38	10.75	5.38	5.82	3.000	3.000	3.000
4"	24.00*	10.00	3.64	3.64	6.88	13.75	6.88	6.84	4.000	4.000	4.000
6"	30.00*	13.50	5.25	5.25	9.00	18.00	9.00	8.91	6.000	6.000	6.000
8"	36.00*	18.00	6.50	6.50	12.00	24.00	12.00	11.81	8.000	8.000	8.000

Dimensions may vary due to design changes. For exact dimensions contact factory.
 *Manual handle lengths do not meet OSHA maximum pull requirements. Other options are available to meet this requirement.

